Tenacious

PRODUCT BRIEFING NOTE

Product Description

K5325 is a Heavy Duty Double Sided Cloth Tape with a calendared natural rubber adhesive and a white siliconized heavy duty release liner.

Product Features

- A very high coat weight of a natural rubber adhesive with a good blend of adhesive and cohesive strength—total gauge of tape is 0.41mm
- The K5325 has a very close mesh synthetic cloth backing
- A heavy weight, siliconized white paper release liner
- Highly credentialled Japanese manufacturer



Benefits

- Excellent conformability to rough textured surfaces like, wood, stone, brick, concrete, textured, flute board
- Clean, easy tear and removes without breaking or leaving a residue
- Good wet-out onto all surfaces as soft enough to readily form a bond
- Despite high tack the cloth backing provides an excellent keying surface so that the product has remarkably good clean-remove characteristics making it suitable for many temporary applications where a high tack is required (often viewed as a "Double Sided Gaffer Tape" due to its shear versatility)
- Due to the high coat weight the upper layer of adhesive and solid cloth protect the lower layer from UV and so works remarkably well outdoors although not intended
- Heavy weight liner strips without breaking

Key Markets

- Sign & Graphics Ideal for mounting of flute board, particularly where clean removal required for temporary signage. Mounting of media on wide range of surfaces but predominantly of a temporary nature — Advertising, Exhibition, Point of Sale & Display
- **Exhibition & Display** Can be used for holding certain heavily textured fabrics down for exhibitions including the temporary holding of synthetic grass
- Film & TV A highly versatile double sided tape for the holding of props & scenery and used as a Double Sided Gaffer Tape
- Building & Construction For the holding and joining of PE sheeting e.g. asbestos removal, render protection. Concrete formwork for holding of fixtures and inserts in place. For the holding of all types of floor coverings both temporary and permanent
- Transport Holding shipping container liners in place for bulk storage of dry products

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out. Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values