

Product Description

KD240 is a translucent woven UV stabilised HDPE cloth All Weather Tape. It has a UV stabilised acrylic adhesive backing to maximise its outdoor life

Product Features

- Woven High Density Polyethylene laminate cloth laminated between two layers of LDPE. The backing is UV stabilised
- A high tack UV stabilised solvent acrylic adhesive system
- Manufactured in Japan by a Division of Mitsubishi Chemical Company
- Available in a standard 25 Metre rolls up to 1,500mm in width (custom lengths possible by negotiation)
- Pending interest we will offer the market a retail version of the KD240 in 48mm or 50mm in 25 Metre length as an outdoor repair tape under the name of "SolarSeal"



Benefits

- ✓ A translucent film that can be hand-torn
- ✓ High tack for sealing and reinforcing applications
- ✓ Excellent UV resistance for outdoor applications
- ✓ Sits flat when smoothed down, this stops weather getting underneath the edge of tape
- ✓ Re-cyclable product as made up of Polyethylene backing only
- ✓ Incredibly versatile repair tape for all situations

Key Markets

- For patching and repair of PE Greenhouses, tarpaulins, groundsheets
- Perfect as a silage patching, repair and joining tape
- Creation of repair patches for a wide range of smooth and textured fabrics but particularly rigid plastics e.g. car headlight and sidelight lens diffusers
- Suitable for use on PVC backed surfaces where a long-term waterproof and air-tight seal required
- PE sheeting strengthening and repair—shrink films, encapsulation, hydroponics
- Use as a "Clear" Gaffer Tape and "All Weather" outdoor repair tape
- Repair and holding of broken glass to stop splinters falling out
- Signage and holding of outdoor graphics
- DIY repairs, recreational and leisure activities such as caravan, camping and marine activities (e.g. sealing cracked skylights, holding damaged trim, repairing split seat covers)

Applications



DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.