

Product Description

KD960 is a Matt Black Resin Cloth Gaffer Tunnel Tape Available in 60mm x 30 Metre rolls with other formats available Ex Overseas 100mm & 150mm



Product Features

- A LDPE/HDPE Wove Cloth/LDPE backing
- A smooth and matte black finish
- A zone coated solvent acrylic adhesive system consists of a 20mm uncoated middle section with 20mm adhesive coating either side
- Easy unwind and tear, across width only
- Unlike most Tunnel Tapes that have a thin film of PE introduced to "deaden" the adhesive, the zone coating method ensures that the outside edges are firm and so there is no gapping making the product easy to apply and ensuring excellent shelf life

Benefits

- ✓ An uncoated central section that covers the cable allowing it to move under the tape. This has a range of significant benefits:
 - a) The cable can move and so reduces the chance of the tape lifting if cable kicked
 - b) The cable has no adhesive residue on it when it is lifted
 - c) Lifts and strips more readily
 - d) Cable can be pulled through and so adjusted even after laying
 - e) Prolongs cable life and prevents residue build-up
- ✓ Very low reflectivity due to its smooth matt surface providing an aesthetic finish
- ✓ Excellent clean-remove characteristics from most surfaces
- ✓ Easily hand torn for easy use
- ✓ High coat weight of adhesive to conform with complex surfaces and wet-out easily
- ✓ The matte finish means it is less prone than gloss tapes for grabbing on synthetic soles of shoes, so less of a trip hazard
- ✓ Compatible for use on vinyl floors
- ✓ Re-cyclable since made from PE resins

Key Markets

- For holding cables in the entertainment industry, film & TV — audio/lighting/staging
- Exhibitions and event management
- Electricians for cable management—cable can be pulled through
- Commercial photographers

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.