

Product Description

S1362 is an Exhibition Grade Double Sided Cloth Tape with an acrylic dispersion adhesive on an easy-tear rayon cloth backing and a white siliconised heavy duty release liner



Product Features

- Developed for the European Exhibition Industry to be compatible with the commonly used temporary flooring surfaces used by the industry
- A differential coat weight of a special acrylic dispersion adhesive with over twice the tack on the lined (carpet tile) side
- A strong but conformable rayon cloth backing that is easy to hand-tear
- A heavy weight, siliconized white paper release liner not prone to tearing on removal
- Sold in 25 Metre length, the standard width for the exhibition trade tends to be 18mm but any width can be cut and a wider width generally recommended for edging applications to prevent trip hazards
- Developed by Orafol, a leading German manufacturer

Benefits

- ✓ Can be used on both concrete, stone, vinyl and wooden surfaces (may work with certain carpet finishes too)
- ✓ Removes without breaking or leaving a residue (Note this applies to stable surfaces but testing always recommended prior to use as any surface treatment can effect performance)
- ✓ Easy to lay and strip liner—ideally used in its 25 Metre length so that do not need to hand-tear the role but scissors or a safe bladed knife may be required
- ✓ Designed to stay stuck to the exhibition surface when remove carpet tiles (this allows the tiles to be stacked without residual adhesive left on them and then finally the tape is lifted — even with forklifts driving over the carpeted surfaces it should lift without breaking)
- ✓ Its acrylic adhesive system makes it particularly suitable for use on vinyl floor finishes

Key Markets

- **Exhibition & Display** For the holding of all types of floor coverings, particularly where clean removal is an important criteria for us
- **Film & TV** A highly versatile double sided tape for the holding of props & scenery and temporary floor coverings
- **Building & Construction** For the holding of PE sheeting e.g. asbestos removal, render protection. For the holding of all types of floor coverings both temporary and permanent e.g. Anti-fatigue matting, retail carpeting and mats
- **Permanent Carpet & Vinyl Laying** The 1362 is particularly suited for the laying of PVC flooring and foam-backed carpets as offers good resistance to plasticisers

DISCLAIMER:

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values

BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.